

# RÜEGG RII Flex-Line



## Allow us to suggest: The new Rüegg RII, the latest addition to the Rüegg family

Here at Rüegg Switzerland, we have been passionately building high-quality fireplaces for over 60 years. Our new products have been setting standards for decades. These qualities are also combined in the new two-sided Rüegg RII, which brings campfire romanticism inside your four walls with its wonderful flame pattern and surprises you with technically refined details.

Whether it's one, two or three-sided, the Rüegg Flex-Line offers state-of-the-art technology and an extensive range of products in ultra-slender design.

**The Rüegg RII, installed in your surroundings by a Rüegg Studio: It is impossible to have more fireside fun!**

More sizzling inspiration can be found here:



[www.ruegg-cheminee.com](http://www.ruegg-cheminee.com)

## The benefits of the new, two-sided glazed Rüegg RII at a glance:

- **User-friendly and functional:** Exceptionally smooth panes stay clean for longer, and can be simply unlatched for cleaning and then clicked back in just one movement – quickly and easily
- **Durability and reliability** in proven Swiss quality: If a repair is required, all movable parts can be replaced without damaging the casing
- **Beautiful flame pattern** due to a clever combustion chamber design and precise combustion air supply
- The flickering flames really come into their own due to subtle and slender **Rüegg Design** with many clever, enhancing details
- The architecture of the Rüegg RII provides **lots of freedom** in the **custom design** of your fireplace
- A certified **convection or storage heating system** and developed for energy-efficient houses
- Efficient **auxiliary heating:** saves oil, gas and money
- Excellent **value for money**
- **High efficiency level** and lower than average emissions
- **Meets all relevant European energy and environmental regulations**

# RÜEGG RII: TECHNICAL DATA

Modell

Rüegg RII



Dimensions:		K
Clear installation opening of hearth H x W x D	cm	50x100x42
Dimensions ceramic glass H x W x D	cm	47x94x37
Door dimensions H x W x D	cm	127x110x56
Gross weight	kg	270
Minimum installation area	cm	> 125x70

Shapes	
--------	--

Technical data		
Nominal power in EN	kW	10.9
Capacity range	kW	10.9-12
System heating performance for encased fireplace design	kW	3.7
Yield under EN tests	%	80.0
CO with 13% O <sub>2</sub> content as per EN tests	mg/m <sup>3</sup>	1125
CO with 13% O <sub>2</sub> content as per EN tests	%	0.09
Fine particles with 13% O <sub>2</sub>	mg/m <sup>3</sup>	39
Gas mass open	g/sec	9.4
Average smoke temperature closed	°C	332
Draft closed	Pa	12
Evacuation	Ø cm	20 (optional 25)

Tests	
EN 13229	✓
BImSchV	Stage 1+2
15-A - Regulation for Austria (01.01.2015)	X
Flamme Verte	(7) *****
Certificato Ambientale	4 stelle
Energielabel	A

Configurations	
Door opening	retractable, fold-out for cleaning
Type of construction (Bauart)	A1/B1 / A2/B2
Separate from ambient air	✓